



Rev. 3.03

## General description

BBSC Capacitor targets Optical communication system such as ROSA/TOSA, SONET and all optoelectronics as well as High speed data system or products. The BBSC is suitable for DC blocking, feedback, coupling and bypassing applications in all broadband optoelectronics and High-speed data system. The unique technology of integrated passive device in silicon, developed by Murata Integrated Passive, offers unique performances with low insertion loss, low reflection and phase stability from 34 KHz to 50 GHz.

These capacitors in ultra-deep trenches in silicon have been developed in a semiconductor process, in order to integrate trench MOS capacitor providing high capacitance value of 47 nF (for kHz–MHz range) and high frequency MIM capacitors for low capacitance value for GHz range), both in a SMT 0201 [0.8 x 0.6mm].

The BBSC capacitor provides very high stability of the capacitance over temperature, voltage variation as well as a very high reliability. BBSC capacitors have an extended operating temperature ranging from -55 to 150°C, with very low capacitance change over temperature (+70ppm/K).

**Assembly:** Suitable for surface mounted application on rigid PCB, ceramic substrate, FR4 (laminated) or flex platforms.

### **Finishing Bump finishing:** ENIG

Copper pads optional for embedding version and SAC305 type 6 for pre-bumping version, as an optional finishing.

## Key features

- Broadband performance to 50 GHz
- Resonance free
- Phase stability
- Insertion loss < 0.3dB Typ. up to 50 GHz
- Ultra-high stability of capacitance value:
  - Temperature 70ppm/K (-55 °C to +150 °C)
  - Voltage <-0.1%/Volt
  - Negligible capacitance loss through ageing
- Low profile: 400µm, 100 µm on request
- Break down voltage: 11V
- Low leakage current
- High reliability
- High operating temperature (up to 150°C)
- Compatible with high temperature cycling during manufacturing operations (exceeding 300 °C)
- Compatible with EIA 0201 footprint

## Key applications

- ROSA/TOSA
- SONET
- High speed digital logic
- Microwave/millimetre system
- High volumetric efficiency (i.e. capacitance per unit volume)
- Broadband test equipment



**Functional diagram**

The next figure provides implementation set-up diagram.




Figure 1 Block Diagram

**Electrical performances**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
C	Capacitance value	@+25°C	-	47	-	nF
$\Delta C_P$	Capacitance tolerance <sup>(1)</sup>	@+25°C	-15	-	+15	%
T <sub>OP</sub>	Operating temperature		-55	25	150	°C
T <sub>STG</sub>	Storage temperature <sup>(2)</sup>		-70	-	165	°C
$\Delta C_T$	Capacitance temperature variation	-55 °C to 150 °C	-	70	-	ppm/K
OV <sub>DC</sub>	Operating voltage <sup>(3)</sup>		-	-	3.8 <sup>(4)</sup> 3.4 <sup>(5)</sup>	V <sub>DC</sub>
BV	Break down voltage	@+25°C	11	-	-	V
$\Delta C_{RVDC}$	Capacitance voltage variation	From 0 V to RV <sub>DC</sub> , @+25°C	-	-	-0.1	%/V <sub>DC</sub>
IR	Insulation resistor	@RV <sub>DC</sub> , +25°C, 120s	-	10	-	GΩ
ESL	Equivalent Serial Inductance	@+25°C, SRF shunt mode	-	10	20	pH
ESR	Equivalent Serial Resistance	@+25°C, shunt mode	-	100	220	mΩ
Fc-3dB	Cut-off frequency at 3dB	@25°C	-	34	40	kHz
IL	Insertion loss	@ 20 GHz, +25°C	-	0.2	-	dB
		@ 40 GHz, +25°C	-	0.3	-	dB
		@ 50 GHz, +25°C	-	0.3	-	dB
RL	Return loss	Up to 50 GHz, +25°C	16	-	-	dB
ESD	HBM stress <sup>(6)</sup>	JS-001-2017	2	-	-	kV

Table 1 - Electrical performances

<sup>(1)</sup>: other tolerance available upon request

<sup>(2)</sup>: without packaging

<sup>(3)</sup>: Lifetime is voltage and temperature dependent, please refer to application note 'Lifetime of 3D capacitors'

<sup>(4)</sup>: 10 years of intrinsic life time prediction at 100°C continuous operation

<sup>(5)</sup>: 10 years of intrinsic life time prediction at 150°C continuous operation

<sup>(6)</sup>: please refer to application note 'ESD Challenge in 3D Murata Integrated Passive technology'



**Module S-parameters of 47nF BBSC in transmission mode**





Figure 2 - 47nF BBSC measurement results (module of S-parameters)

**Schematic of 47nF BBSC in transmission mode**



**6.6-mil Rogers 4350B.**

Microstrip mode – line width = 0.40 mm and gap = 0.300 mm. (nominal 50 ohm characteristic impedance).

Figure 3 – 47nF BBSC measurement schematic

**Example of surface mounted 0201**




Figure 4 – micro picture of BBSC mounted on board in coplanar mode



**Pinning definition**




Figure 5 Pinning definition

pin #	Symbol	Coordinates X / Y
1	Signal	-225.0 / 0.0
2	Signal	225.0 / 0.0

Table 2 - Pinning description. Reference (0,0) located at the centre of the die.

**Ordering Information**

Part number	Package		
	Packaging <sup>(1)</sup>	Finishing	Description
939113493547-T3N	7" T&R (1 000 pieces/reel) <sup>(3)</sup>	ENIG <sup>(2)</sup>	BBSC 0201 - 47nF – 2 pads – 0.8 x 0.6 x 0.40mm <sup>(4)</sup>
939114493547-T3N	7" T&R (1 000 pieces/reel) <sup>(3)</sup>	ENIG <sup>(2)</sup>	BBSC 0201 - 47nF – 2 pads – 0.8 x 0.6 x 0.10mm <sup>(4)</sup>
939114493547-T5N	7" T&R (5 000 pieces/reel) <sup>(3)</sup>	ENIG <sup>(2)</sup>	BBSC 0201 - 47nF – 2 pads – 0.8 x 0.6 x 0.10mm <sup>(4)</sup>
939114493547-T3S	7" T&R (1 000 pieces/reel) <sup>(3)</sup>	SAC <sup>(2)</sup>	BBSC 0201 - 47nF – 2 pads – 0.8 x 0.6 x 0.10mm <sup>(4)</sup>
939114493547-T5S	7" T&R (5 000 pieces/reel) <sup>(3)</sup>	SAC <sup>(2)</sup>	BBSC 0201 - 47nF – 2 pads – 0.8 x 0.6 x 0.10mm <sup>(4)</sup>

Table 3 - Packaging and ordering information

- (1) Other film frame carrier are possible on request
- (2) SAC = ENIG (0.1µm Au / 5µm Ni) + SAC305 type 6 or ENIG 0.1µm Au / 5µm Ni
- (3) missing capacitors can reach 0.5%
- (4) Refer to **Erreur ! Source du renvoi introuvable.** 9

Product Name	Die Name	Description
BBSC493.547	UC0201547	BBSC 47nF/0201/BV11V – 2 pads – 0.8 x 0.6 mm x 0.40mm
BBSC493.547	UC0201547	BBSC 47nF/0201/BV11V – 2 pads – 0.8 x 0.6 mm x 0.10mm

Table 4 - Die information



**Pad Metallization**

This surface mounted Silicon Capacitor is delivered as standard with ENIG (0.1µm Au / 5µm Ni) (Refer to Figure 6)

Other Metallization, such as SAC305 type 6 bumping (Refer to Figure7). Copper, Thick Gold or Aluminum pads are possible on request.

Silicon dies are not sensitive to humidity, please refer to applications notes ‘Assembly Notes’ section ‘Handling precautions and storage’.




Figure 6 – Top electrode description of ENIG finishing version



Figure 7 – Top electrode description of SAC305 pre-bumped version

**Material regulation**

This product is RoHS compliant at the time of publication. For further information about regulation compliancy, please ask your sales representative.

**Package outline**

The product is delivered as a bare silicon die.




Figure 8 - Package outline drawing




Figure 9 - Package outline drawing




Figure 10 - Package isometric view

	L (mm)	W (mm)	T (mm)	a (mm)	P (mm)	eb (mm)	t (mm)
Component dimension	0.80 ±0.024	0.60 ±0.04	0.41 max or 0.11 max	0.15	0.30	0.40	0.04 <sup>(1)</sup> 0.05 <sup>(2)</sup> 0.005 <sup>(3)</sup>
Landing pad recommendation	/	/	/	0.164 min	0.186 max	0.286 min	/

(1) Standard with solder joint height after reflow on board with mirror pads.  
 (2) Standard with solder bump height before assembly  
 (3) Only in case of ENIG finishing



**Assembly**

The attachment techniques recommended by Murata on the customer’s substrates are fully detailed in specific documents available on our website. To assure the correct use and proper functioning of Murata capacitors **please download the assembly instructions on <https://www.murata.com/en-us/products/capacitor/siliconcapacitors> and read them carefully.**



Figure 11 Scan this QR Code to access the Murata Silicon Capacitor web page

**Packaging format**

Please refer to application note ‘Products Storage Conditions and Shelf Life’.

**Tape and Reel:**

Dies are flipped in the tape cavity (bump down) with die ID located near the driving holes of the tape.




Figure 12 - Reel drawing

Tape Width	Diameter A	C	D	Hub N	W1	W2
8	178 (7 inches)	13.5	20.2	60	9.3	11.5

Table 5 – Reel dimensions (mm)




Figure 13 - Tape drawing

Cavity dimensions			Carrier tape width W0	Carrier tape pitch P0	Quantity per reel	Die thickness
A0	B0	K0				T(mm)
0.76	0.96	0.22	8	2	1 000	100 $\mu$ m
0.74	0.94	0.57	8	4	1 000	400 $\mu$ m

Table 6 - Tape dimensions (mm)

## Definitions

Data sheet status

**Objective specification:** This data sheet contains target or goal specifications for product development.

**Preliminary specification:** This data sheet contains preliminary data; supplementary data may be published later.

**Product specification:** This data sheet contains final product specifications.

Limiting values

Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or any other conditions above those given in the Electrical performances sections of this specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information

Where application information is given, it is advisory and does not form part of the specification.

## Revision history

Revision	Date	Description	Author
Release 1.00	2016 November 07th	Objective specification	OGA
Release 2.01	2018 June 27th	Relative to PCN	OGA
Release 3.00	2021 June 27th	Product release	OGA, DDE, SCA, SYO, DYU, LLR
Release 3.01	2022 Jan. 19th	Remove FFC packing	OGA
Release 3.02	2023 December 19th	Extended high limit frequency / Updated packing	DYE
Release 3.03	2025 October 20th	Ordering information has been updated according to the latest product lineup and specification.	HFU - CGU

## Disclaimer / Life support applications

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Murata customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Murata for any damages resulting from such improper use or sale.

Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.

Murata Integrated Passive Solutions S.A. makes no representation that the use of its products in the circuits described herein, or the use of other technical information contained herein, will not infringe upon existing or future patent rights. The descriptions contained herein do not imply the granting of licenses to make, use, or sell equipment constructed in accordance therewith. Specifications are subject to change without notice.



[www.murata.com](http://www.murata.com)

[mis@murata.com](mailto:mis@murata.com)